


# Blair Corporation

Manufacturer and Distributor

Wire Rope · Hardware · Chain · Cable Railing ·  
Structural Strand Assemblies · Cordage · Castings · Forgings·

## ROTATION RESISTANT 19 X 7 CLASS



Specification: RR-W-410D

8 x 7+FC and 19 x 7 Rotation Resistant

Extra Improved Plow Steel Uncoated and Drawn Galvanized

Rope Diameter		Approx. Weight		Nominal Breaking Strength	
Nominal (minimum)	Maximum	FC	WSC	Uncoated	Galvanized
inches	inches	lb/ft	lb/ft	lb	lb
3/8	0.394	0.24	0.25	11,080	11,080
7/16	0.459	0.33	0.35	15,000	15,000
1/2	0.525	0.43	0.45	19,440	19,440
9/16	0.591	0.55	0.58	24,400	24,400
5/8	0.656	0.68	0.71	30,200	30,200
3/4	0.788	0.87	1.02	43,200	43,200
7/8	0.919	1.32	1.39	58,500	58,500
1	1.050	1.73	1.82	76,000	76,000

Available in Larger Diameters

[www.BlairWireRope.com](http://www.BlairWireRope.com)

3610 Palomar Valley Dr  
Spring, Texas 77386

Phone: 832-928-9655 · Fax: 281-528-0394